

4/A
RS
8-30-01

S/N UNKNOWN

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Longoni Serial No.: UNKNOWN
Filed: CONCURRENT HEREWITH Docket No.: 975.330USW1
Title: FRAME CONTROL METHOD AND APPARATUS

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL733009995US

Date of Deposit: 4 April 2001

I hereby certify that this correspondence is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

By: Susan Henig

Name: Susan Henig

PRELIMINARY AMENDMENT

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Please enter the following preliminary amendment into the above-referenced application.

ABSTRACT

Please insert the attached abstract into the application as the last page thereof.

CLAIMS

Please delete claims 1-12. Please insert the following claims 13-24.

13. A frame control method for controlling a transport frame used for transmitting a data unit (**TB**) via a dedicated channel between network elements (**2, 3; 10**) of a communication system having different types of connections, comprising the steps of:
- (a) encapsulating said data unit (**TB**) into said transport frame;
 - (b) selecting a frame type coding of said transport frame in accordance with a connection type of said dedicated channel; and

(c) maintaining information on the frame types to be used for data units on a dedicated channel.

14. A frame control method according to claim 13, wherein said frame type coding defines specific control information fields of the transport frame and its bit number.

15. A frame control method according to claim 14, wherein said specific control information fields include a transport format indicator field the bit number of which is determined on the basis of the number of different transport format indicators allowed for said dedicated channel.

16. A frame control method according to claim 15, wherein the value of said transport format indicator field defines if and how a whole original data unit set is split into different data units to be transported via said dedicated channel.

17. A frame control method according to claim 17, wherein the value of said transport format indicator field defines the presence and/or bit number of another one of said specific control information fields.

18. A frame control method according to claim 17, wherein said other one of said specific control information fields is a frame reliability information field which is provided when the value of said transport format indicator field indicates a high bit rate transmission.

19. A frame control method according to claim 13, wherein said frame type coding is selected in a set-up phase of said dedicated channel based on corresponding set-up parameters of said dedicated channel.

20. A frame control method according to claim 13, wherein said frame type coding does not include a channel indicator field, if one transport connection is allocated to said dedicated channel.

21. A frame control method according to claim 13, wherein said frame control method is used in a user plane interface of a WCDMA system.

22. A frame control method according to claim 21, wherein said dedicated channel is an AAL 2 channel and said data unit is a user plane data unit.

23. A frame control apparatus for controlling a transport frame used for transmitting a data unit **(TB)** via a dedicated channel between network elements **(2, 3; 10)** of a communication system having different types of connections, comprising:

- (a) means **(12)** for encapsulating said data unit **(TB)** into said transport frame;
- (b) means **(13)** for selecting a frame type coding of said transport frame in accordance with a connection type of said dedicated channel, and
- (c) means for maintaining information on the frame types to be used for data units on a dedicated channel.

24. A frame control apparatus according to claim 23, wherein said network elements **(2, 3; 10)** comprise a base station subsystem **(2)** and a radio network controller **(3)** of a mobile communication system **(6)**.